

Organic Pollutant Monitor (UV Meter)

OPM-1610

The OPM-1610 is one of our latest models, and represents the culmination of more than three decades of product development and field experience. This model is an organic pollutant monitor (UV meter) that adopts ultraviolet absorptiometry to analyze the organic pollution levels in commercial, industrial, and other types of effluents. The values obtained are correlated with the COD.

Before using the instrument, make a correlation between the instrument output and the COD.



Features

Environmentally-friendly, reagentless measurement
This model measures COD without using mercury or hexavalent chromium reagents.

Continuous measurement ideal for effluent water monitoring.

By continuously measuring COD, abnormality in the effluent can be detected quickly, enabling prompt handling of the situation.

Compact and lightweight design

The immersion-type detector included with the instrument, which was highly rated by users of the previous model, has been made approximately 50% smaller and 20% lighter than the original detector, making it much easier to install the instrument. In addition, the installation of the optional sample receiving tank enables measurements to be performed by extracting samples from the process stream.

New optical system

A new highly stable light source ensures that the unit provides stable measurements.

The new optical system employs a power-saving lamp and eliminates the need for a heater to stabilize the light source. These two factors help to significantly reduce the amount of power consumed by the instrument (approximately 80% less than the previous model). Furthermore, additional power savings is also possible by using an immersion-type detector that does not require a sample pump system.

Standard Specifications

Product name	: Organic pollutant Monitor (UV meter)
Model	: OPM-1610
Object measured	: Organic pollutant in commercial, industrial, and other types of effluents
Measurement method	: Dual-wavelength absorptiometry (UV 254nm/visible light 660nm)
Measurement range	: UV absorbance; 0~2.5Abs (The transmission output range can be adjusted in 0.1 Abs increments within a range of 0.5~2.5Abs.) The readings can be displayed as absorbance on a 10 mm cell length conversion basis. The displayable absorbance ranges are as follows. 25 mm cell; 0~1.0Abs 10 mm cell; 0~2.5Abs 6 mm cell; 0~4.17Abs
Measurement cell	: Immersed parallel cell (6, 10, or 25mm, as specified by customer)
Cell cleaning	: Wiper system for automatic cleaning Cleaning cycle; 1~9999 minutes (default; 60) No. of cleaning; 0~99 (default; 2)
Sample Condition	: Sample temperature; 0~45°C (no freezing) Flow speed (Immersion type); Lower 0.75m/sec. (Notes of Installation on Page of 7 and 9) Flow rate(Sampling type); 3~6 L/min.
Maximum water depth	: 6m

Calibration	: Zero; Pure water	
Displayable item	: UV-VIS absorbance, UV absorbance, VIS absorbance, COD conversion value, Turbidity conversion value, SS (Suspended Solid) concentration conversion value and sample temperature.	An approximately five year block of data can be saved when 1 minute is specified as the sampling cycle. If the amount of available free space becomes incredibly low, the unit will be unable to record new data. Make sure to delete old or unnecessary data at regular intervals.
Transmission output	: 4~20mADC, load resistance; 600Ω or less, isolated Simultaneously output of any three of the following signals; UV-VIS absorbance, UV absorbance, VIS absorbance, COD conversion value, turbidity conversion value, SS concentration conversion value, and sample temperature (non-isolated between transmission outputs). The COD conversion value, turbidity conversion value, and SS concentration conversion value are calculated by employing a linear expression to convert the absorbance.	Power requirements: 100~240VAC±10%, 50/60Hz Power consumption: Average of approx. 10VA, maximum of approx. 20VA
		Mounting : Immersed type, wind-up type, hanging type, and sampling type
		Materials : Transmitter; Die-cast aluminum Detector; Main body...SUS316, ABS resin Cell...Quartz glass Wiper...FPM rubber
		Surface finish : Transmitter; Metallic silver
		Protective construction : Transmitter; IP65
Contact output signals	: Power cut-off signal, CO(Change-Over)contact (NO/NC) output Alarm signal, NO(Normally-Open)contact (NO) output (Any three of the following contacts can be selected.) Under maintenance Under cleaning General alarms Measured value higher limit alarm Lamp error (UV, VIS) No sample Leakage alarm Wiper drive motor error Sample temperature error In addition to the first three items listed above, any three of the six general alarm items can be assigned to contact outputs 1~3. Contact capacity; 30VDC, 0.1A or less 125VAC, 0.1A or less (resistance load)	Transmitter cable : Six cable glands for ø6~12 cable (one of which is for the detector) Conduit threads (six G1/2 threads) can be connected when the cable glands are removed.
		Extension cable : 1 cable to connect the detector and transmitter Standard length; Sampling type...3m. Immersed type, wind-up type, and hanging type; Specified by customer Maximum length; 30m (optional feature)
		Dimensions (see the section "Dimensions" for details) : Transmitter; Approx. 181 (W) x 95 (D) x 180 (H) mm Detector; Approx. 150 (W) x 95 (D) x 455 (H) mm The height (H) of the immersed type varies according to the specification.
		Weight : Transmitter; Approx. 2.0kg Detector; Approx. 5.3kg(except cable)
		Installation : Unit can be installed outdoors Ambient temperature; -5~50°C Ambient humidity (transmitter); 95% RH or less
Contact input signals	: Cleaning start signal; Signal used to remotely control the cleaning program. No-voltage contact signal ON resistance; 50Ω or less Short circuit current; Maximum of 5mA Open voltage; 24VDC Make time; 0.1sec. or more	Ensure the unit is not subjected to vibration, shock, and corrosive gases. Install the detector at a position in which the sample water can circulate smoothly. This will ensure that the readings accurately reflect the sample values.
Digital communication output (optional feature)	: Two selections are available for digital communication output; communication output RS-485 or output to USB memory for data recording. Digital communication output; RS-485 interface USB memory (data is saved in CSV format) Memory data format; date-hour-minute, UV, VIS, and UV-VIS values, COD conversion value, turbidity conversion value, SS concentration conversion value, water temperature (sampling cycle can be set to a length of 1 to 999 minutes)	

Performance

UV absorptiometry linearity : Within $\pm 2\%$ FS


UV absorptiometry repeatability : Within $\pm 2\%$ FS

UV absorptiometry zero drift : Within $\pm 2\%$ FS/week

UV absorptiometry span drift : Within $\pm 2\%$ FS/week

Response rate : Within 30 sec. for 90% response

Operating principle



The OPM-1610 uses the dual wavelength technique to measure pollutants. This technique adopts two highly stable sources of light, UV (ultraviolet) and VIS (visible light).

When a UV light source is applied, a 254nm emission line from the ozone-free low pressure mercury lamp is used. In VIS detection, a pulsating 660nm LED is irradiated as the light source.

There are two ways for converting instrument output to


COD values. The first consists of using the correlation between the UV absorbance (A_{UV}) and the COD manual analysis value. The second method entails using the correlation between the difference of the “UV absorbance (A_{UV}) minus VIS absorbance (A_{VIS})” (value given by the expression $A_{UV} - a \times A_{VIS}$ to eliminate the effect of suspended solids) and the COD manual analysis value.

a = Correction factor (Freely specified)

Terminal connections

Any three of the following six items can be assigned to contact outputs 1-3:


- UV value (Abs)
- VIS value (Abs)
- UV-VIS value (Abs)
- COD conversion value
- Turbidity conversion value
- SS concentration conversion value




Terminal screw size: M3
Dedicated connector is used for connecting between the detector and transmitter.

Dimensions Unit : mm

● Mounted on a pole



● Mounted on a wall or rack



● Hood (optional)

Recommended when installing the instrument outdoors at a location exposed to direct sunlight.

Material : SUS304


Mounting : 50A pipe or wall

Code number : 7049930K


Dimensions

Unit : mm


● Immersed type detector




● Wind-up type detector
(1 guide pipe system)




(2 guide pipe system)



● Hanging type detector



● Sampling type detector



Product code

● Wind-up type/Hanging type

OPM1610-2-	<input type="checkbox"/>								
	1								Transmitter mounting
	2								50A pipe
									Wall
									Digital output
	0								None
	1								RS-485
	2								USB memory
									Arrester (power line/transmission line)
	0								None
	1								Included
									Hood for transmitter (sun shade)
	A								None (standard)
	B								Equipped
									Detector cell length
	1								25 mm
	2								10 mm
	3								6 mm
									Installation
	0								No pole stanchion
	1								Pole stanchion (ZB1-1-B2: SUS304)
									Detector mounting *1
Custom specification code:		E							Wind-up device (1 guide pipe system), 2m *1
Numeric digit: 9		F							Wind-up device (1 guide pipe system), 3m *1
Alphabet: Z		G							Wind-up device (1 guide pipe system), 4m *1
		H							Wind-up device (2 guide pipe system), 2m *2
		J							Wind-up device (2 guide pipe system), 3m *2
		K							Wind-up device (2 guide pipe system), 4m *2
		L							Wind-up device (2 guide pipe system), 5m *2
		M							Wind-up device (2 guide pipe system), 6m *2
		N							Use existing wind-up device (1 guide pipe system) *3
		P							Use existing wind-up device (2 guide pipe system) *3
		Q							Hanging type (two 3.5m chains included) *4
									Zinc plates *5
	0								N/A
	1								Equipped
									Cable length (between transmitter and detector)
	2								5m
	3								10m
	8								Custom spec. (max. 30m)
									Markings
	1								Japanese (standard)
	2								English





- *1. The condition of the sample water flow velocity for the wind-up device (1 guide pipe system) must be 0.75 m/sec or less. When the flow velocity exceeds 0.3m/sec, make sure to secure the lower end of the guide pipe before using the device. (See the installation diagram.)
- *2. The wind-up device (2 guide pipe system) must be used at a flow velocity of 1.0m/sec or less. Make sure to secure the guide pipes at multiple points along the pipes and at the lower end before using the device.
The frame of the wind-up device is made of SUS304 (coated). In custom specifications, a winch made of SUS can be selected. However, the position of the handle is reversed left to right. (Same for *1 and *2)
- *3. The existing wind-up device for OPM-410 / OPM-410A is used for mounting the detector.
- *4. The recommended method for simple installation is using two 3.5m chains to lower the detector. (Two eye bolts are supplied with the detector when this method is used.)
The flow velocity must be 0.75m/sec or less.
- *5. If the water sample becomes contaminated, with sea water for example, it can result in the introduction of a high concentration of electrolytes or residual iron-based coagulants into the sample. This may increase the possibility of the detector rusting away rapidly.
If that is the case, select "Equipped" for Zinc plates.
Also select "Equipped" for the Zinc anodes section when you replace existing equipment that already has zinc plates equipped.

Notes




- 1: The transmission output range can be adjusted in 0.1Abs increments within a range of 0.5~2.5Abs.
In the default factory configuration, the output signals for 0~1.0Abs are output at between 4~20mA, regardless of the cell length.
- 2: The user can select whether the absorbance is "Displayed" or "Not displayed" on a 10mm cell length conversion basis.
In the factory default configuration, the absorbance is "Not displayed" on a 10mm cell length conversion basis.
- 3: The unit is powered by an adjustable-voltage 100~240VAC power supply.
- 4: Any three of the following output signals can be selected: UV-VIS absorbance, UV absorbance, VIS absorbance, COD conversion value, turbidity conversion value, SS concentration conversion value, and sample temperature (4~20mADC).
- 5: When you replace existing equipment, the specifications for alarm contact output and other items for this unit might differ from the old unit. For details, please contact one of our sales representatives.

Installation diagram Unit : mm

● Sampling type (mounted on pole stanchion)




● Sampling type (mounted on aluminum frame)



Product code

● Sampling type



- *1. A calibration vessel is equipped as a standard.
- *2. The aluminum frame has the same dimensions as the base of our previous models (OPM-410 and OPM-410A). Thus, the frame of a previously released instrument can be used to replace the frame of this new instrument.
- *3. If the water sample becomes contaminated, with sea water for example, it can result in the introduction of a high concentration of electrolytes or residual iron-based coagulants into the sample. This may increase the possibility of the detector rusting away rapidly.
 If that is the case, select "Equipped" for Zinc plates.
 Also select "Equipped" for the Zinc plates section when you replace existing equipment that already has zinc plates equipped.

Notes

- 1: The transmission output range can be adjusted in 0.1 Abs increments within a range of 0.5~2.5Abs. In the default factory configuration, the output signals for 0~1.0 Abs are output at between 4~20mA, regardless of the cell length.
- 2: The user can select whether the absorbance is "Displayed" or "Not displayed" on a 10mm cell length conversion basis. In the factory default configuration, the absorbance is "Not displayed" on a 10mm cell length conversion basis.
- 3: The unit is powered by an adjustable-voltage 100~240VAC power supply.
- 4: Any three of the following output signals can be selected: UV-VIS absorbance, UV absorbance, VIS absorbance, COD conversion value, turbidity conversion value, SS concentration conversion value, and sample temperature (4~20mADC).
- 5: When you replace existing equipment, the specifications for alarm contact output and other items for this unit might differ from the old unit. For details, please contact one of our sales representatives.



DKK-TOA CORPORATION

Overseas Sales Division:
DKK-TOA Corporation
29-10, 1-Chome, Takadanobaba, Shinjuku-ku,
Tokyo 169-8648 Japan
Tel : +81-3-3202-0225 Fax : +81-3-3202-5685



CAUTION

Please read the operation manual carefully
before using products.

<http://www.toadkk.co.jp/english>

Information and specifications are subject to change without notice.

Issued on 8/6/2016